

Sound Supremacy!

Nick

2 Year Warranty

OUTPUT POWER @ 14.4V input		DAMPING FACTOR @100Hz 4 ohm	> 300
RMS per channel at 4 Ohms	625 x 1 CH	CROSSOVER RANGE	
RMS per channel at 2 Ohms	1250 x 1 CH	High Pass, 12dB/Octave	N/A
RMS Bridged Mono at 4 Ohms	N/A	Low Pass, 24dB/Octave	10Hz - 250Hz
RMS Mono at 1 Ohm	2500 x 1 CH	Subsonic	15Hz - 55Hz
INPUT SENSITIVITY	200mV - 6.0V	Variable Bass Boost (0 to + 12 dB bass boost at 50 Hz)	Yes
FREQUENCY RESPONSE	10Hz - 250Hz +/- 0.5dB	Wired remote bass control included	Yes
THD	LESS THAN 0.5%	Phase Shift (0 - 180 degrees)	Yes
S/N RATIO	> 105 dB	Fusing (not supplied)	External 250A
CHANNEL SEPARATION	N/A	Size (L x W x H) in	19.7 x 8.4 x 2.2

You're not a kid anymore!

Features

- 1 x 2500 Watts RMS @ 1 Ohm
- Thermally Stable Heat Sink design for maximum heat transfer efficiency
- Extra Large Gauge Terminals for show quality installations
- Extreme Bulk capacitor banks for High Power Stability
- Designed with the latest Technology in Ultra Efficient Class D design
- Butterworth Crossover Filters for serious high-end performance
- Docking Pads® to reduce vibration and extend the life of your amplifier
- DC, Short Circuit, Thermal and Overload Protection
- Diagnostic LEDs