



Sound Supremacy!

Wendy

2 Year Warranty

OUTPUT POWER @ 14.4V input		DAMPING FACTOR @100Hz 4 ohm	> 100
RMS per channel at 4 Ohms	75 W x 2 CH	CROSSOVER RANGE	
RMS per channel at 2 Ohms	125 W x 2 CH	High Pass, 12dB/Octave	80-1.2K Hz
RMS Bridged Mono at 4 Ohms	250 W x 1 CH	Low Pass, 24dB/Octave	10Hz - 250Hz
RMS Mono at 1 Ohm	N/A	Subsonic	N/A
INPUT SENSITIVITY	200mV - 6.0V	Variable Bass Boost (0 to + 12 dB bass boost at 45 Hz)	No
FREQUENCY RESPONSE	10Hz - 30Hz +/- 0.5dB	Wired remote bass control included	No
THD	LESS THAN 0.01%	Phase Shift (0 - 180 degrees)	No
S/N RATIO	> 95 dB	Fusing	1 x 30A
CHANNEL SEPARATION	>85 dB	Size (L x W x H) in	7.5 x 8.9 x 2.2

A Portrait of Audio Performance!

Features

- 75 Watts RMS X 2 @ 4 Ohm
- Angled Terminals for show quality installations
- Old School Full Complimentary low distortion Class AB design
- Butterworth Crossover Filters for serious high-end performance
- Docking Pads® to reduce vibration and extend the life of your amplifier
- DC, Short Circuit, Thermal and Overload Protection
- Diagnostic LEDs